



H.M.I.S. RATING	
Health	1
Flammability	0
Reactivity	0
Protective Equip.	E

## Material Safety Data Sheet – OSHA 174

### Material Safety Data Sheet

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

### US Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB No. 1218-0072

## MasterSeal MTR –Rubberized Asphalt Emulsion Sealcoat

### SECTION I - Manufacturer / Product Information

<b>Manufacturer's Name:</b> SealMaster- Phoenix	<b>Emergency Telephone No.:</b> Chemtrec: 1-800-424-9300
<b>Address:</b> 2020 W. McDowell St. Phoenix, AZ 85009	<b>Telephone Number for Information:</b> 1-877-253-4670
	<b>Date Prepared:</b> October 27, 2011

### SECTION II - Chemical Identity Information

Ingredient	CAS #	OSHA PEL	ACGIH TLV	Other Limits	Percent
Bentonite Clay	1302-78-9	15 mg/m3	10 mg/m3		
Ball Clay	1332-58-7	10 mg/m3	N/A		
Asphalt	8052-42-4	N/A	5 mg/m3		
Ground Tire Rubber	N/A	N/A	N/A		
Napthenic/Aromatic Oil	64742-04-7	N/A	N/A		
Carbon Black	1333-86-4	3.5 mg/m3	3.5 mg/m3		
Mineral Aggregate	N/A	N/A	N/A		

### SECTION III - Physical / Chemical Characteristics

<b>Boiling Point:</b> 100° Celsius (212° Fahrenheit)	<b>Specific Gravity (H2O = 1):</b> 1.17
<b>Vapor Pressure (mm Hg):</b> Nearly equal to water.	<b>Melting Point:</b> N/A
<b>Vapor Density (AIR = 1):</b> <1	<b>Evaporation Rate (Butyl Acetate = 1):</b> Approximately 1.8
<b>Solubility in Water:</b> Easily dispersible in the liquid state.	
<b>Volatile Organic Content:</b> Contains less than 10 g/l, or 0.8% by volume VOC	
<b>Appearance and Odor:</b> Black liquid, asphaltic odor.	

### SECTION IV - Fire and Explosion Hazard Data

<b>Flash Point (Method Used):</b> N/A	<b>Flammable Limits:</b> N/A	<b>LEL:</b> N/A	<b>UEL:</b> N/A
<b>Extinguishing Media:</b> Foam, CO2, dry chemical, water fog, other.			
<b>Special Fire Fighting Procedures:</b> Full protective equipment, including self-contained breathing apparatus to be worn. Water cool sealed containers in area of fire to prevent rupture due to steam generation.			
<b>Unusual Fire and Explosion Hazards:</b> N/A			

### SECTION V - Reactivity Data

<b>Stability:</b> Unstable: Stable: X	<b>Conditions to Avoid:</b> Keep from freezing and extreme heat.
<b>Incompatibility (Materials to Avoid):</b> Strong oxidizers.	
<b>Hazardous Decomposition or Byproducts:</b> Combustion may yield fumes, smoke, carbon monoxide, carbon dioxide and other toxic pyrolysis products.	
<b>Hazardous Polymerization:</b> May Occur: Will Not Occur: X	<b>Conditions to Avoid:</b> N/A

